



NoteCart NEXT 36 is a mobile storage and charging solution for 36 units.

NoteCart NEXT is a mobile, compact cabinet for storage and charging of iPads, tablets, laptops, Chromebooks and similar devices. The 4 wheels on the NoteCart NEXTseries have been carefully selected to complement the rest of the design so that NoteCart rolls easily, regardless of weight of the many devices and the type of floor under the mobile cabinet. Wheels with ball bearings and soft rubber coating which, in use, maintain and restores the rounding of the wheel.

During operation, all electronics are stored in the locked compartment behind the cabinet, so that only the IT manager has access to them. A secure cable management system ensures that the cables stay in the cabinet once they have been installed. The main panel which divides power connectors into groups of 9, with sequential control with a 3 second time interval. This is to ensure unnecessary overloading when connected to the main switch.







NoteCart NEXT 36

SOLUTIONS

- Designed for storage, charging and transport of up to 36 laptops (15"), Chromebooks, tablets, iPads or Similar devices.
 - The cabinet is sturdy and easy to transport on its rubber wheels, which have been thoroughly tested.
- Strong handles on the sides make it easy to push and move the cabinet.
- The cabinet has a cable system which ensures that the cables do not disappear and that they are stored clutter-free.
- The locks on the front and rear doors ensure that the devices are stored safely.

DEVICES

Laptops (15"), Chromebooks, tablets, iPads and similar devices See compartment dimensions on page 3.

ACCESSORIES

NoteSecure Item no. NC-O-SECURE

ITEM NUMBER

10000209 NoteCart NEXT 36 black 10000208 NoteCart NRXT 36 white















leba-innovation.com



NoteCart NEXT 36 Technical specifications

EXTERIOR DIMENSIONS		OPTIONS
Width (incl. handle)	703 mm (883 mm incl. handl)e	NOTE: handle has to be fitted.
Depth	652 mm	
Height	852 mm	
WEIGHT	58 kg	
DIMENSIONS SHELVES	36 deviders	
Width	27 mm	
Depth	430 mm	
Height	300 mm	
CONNECTING CABLE	1.8m Schuko/DK	
VENTILATION	Passive ventilation	
ELECTRONICS		
Main panel	230V 50/60Hz 16A in 10A out max 3680W sequential start 3 sec.	
Power panel	4x9 connectors, 250V AC, 50/60Hz, 10A, 2500W max	
LOCKING SYSTEM FRONT	3 point locking system with a key	
LOCKING SYSTEM	Standard Lock 180	
WHEEL SPECIFICATIONS	Elastic rubber wheels with ball bearings. 150 kg max weight p Dia. 100 mm. EN-2532 Cert.	er wheel
PACKAGING	Honeycomb recycled cardboard	
WEIGHT PACKED	65 kg (individually packed incl. pallet)	
DISPOSAL	According to local standards	

leba-innovation.com