factsheet

s26 C sCharge PoE P+D USB-C



Product name	sCharge PoE P+D USB-
Short name	s26 C
EAN code	4260258612264
Manuf. part no.	sCh-PoE-P+D-C-1.0
Description	 PoE+ to USB-C Power and Data Delivery solution for iPad Pro Gen 3, Microsoft Surface Go, Samsung Galaxy Tab Active, Google Pixel Phones and others! Compatible with IEEE 802.3at PoE+ Switch or Injector. Includes a Bi-Directional USB-C cable. Allows you to place your device where you want. Extend power and data up to 100m. Converts IEEE 802.3af PoE to 5 Volts 13 Watts max Wired data through the USB-C connector allows for greater network security Optimized for fast charging and better throughput Plug-and-play design for easy installation for home or business applications
Technical Data	Input voltage48-56VData Rate(Input) 10/100/1000 Gigabit / (Output) 10/100 MbpsData StandardUSB 2.0 (Output)LEDs Per PortGreen (POE) / Yellow (USB-C)Max Power for Kit25 WattsMount TypeWall or DIN rail (sold separately)Operating Humidity-10 - 60COutput Voltage5V,2.6A; 9V,1.78A; 12V,1.34A; 15V,1.37A; 20V,1.15APoE MethodIEEE 802.3atPoE StandardIEEE 802.3atAdapters includedUSB-C to USB-C Right Angle Bi-directional cableConnector TypesUSB-CWeight90g (3 oz.)
Compatible	
	Supports iPad Pro Gen 3, Microsoft Surface Go, Samsung Galaxy Tab Active, Google Pixel Phones
Applications	Ideal for Zoom Room, Gotomeeting, Webex, Skype and other Video Conferencing POS Stations and Kiosks, Schedulers and Mounted tablets
Dimensions	114 x 51 x 25 mm (4.5 x 2. x 1 inch), cable length 45 cm (~1.5 feet)
Customs tariff no.	CN/8504 4090
Country of origin	China



Heilige Stoel 6807 6601 SV Wijchen The Netherlands info@sediso.com +31(0)24-6419474