

PARAPROJECT®

Case UC20 UltraCharge

Protect , TwinCharge , Transport , Sync



Part denomination	PARAPROJECT Case UC20 UltraCharge USB-PD with USB-C®, without cable, black
Part number	208700151
GTIN /EAN	4006793003071
Field of application	Education
Certificates	CE
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024
Scope of delivery	- 1x Case UC20, LED, with integrated high-performance USB-PD Power Delivery - 1x device connecting cable, EU, length: 5m - 1x operating instruction for case and combination lock
Materials	- X-ABS plastic
External dimensions (WxDxH)	720 mm x 390 mm x 550 mm
Weight	15500 g
Transport dimensions	760 mm x 420 mm x 570 mm
Dimensions of euro-pallets	1200 mm x 800 mm x 1860 mm
Number of euro-pallet	6
customs tariff number	85044082
Country of origin	RO
Fittings	- case lid with zipper pocket, cable pocket and keep-safe compartment - case body with sync and charging unit, storage compartment for 20 tablets, storage compartment for e.g. Access Point - additional ventilation openings in the case lid and bottom for optimal air circulation - temperature sensor, main switch, active fans - 20x LED displays per port, showing the current charging status of each device
Compatible devices	all tablets / chromebooks / ultrabooks up to 12" / MacBook Air 13.3"
Max. number of devices	20
Operating system	iOS / Android / Windows
Cable types for equipment	USB-C
Power supply	central power pack supplies power for all the modules
Output power per port	automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; supports "Quick Charge" ; e.g. 20x Surface Go2 10.5" tablets with 24 W each per port, or 20 x iPad Pro / Air (with USB-C) with 22W each per port ; 20x MacBook Air 13.3" with up to 30W per port ; 5,9,10,12,15V/3A; 20V/2.25A
Optional accessories	- USB-Typ-C socket (sync function only usable when combined with adequate MDM software and device configuration, software not included) - USB-C to C cable, 0.3m length
Lock types	combination lock

PARAPROJECT®

Case UC20 UltraCharge

Protect , TwinCharge , Transport , Sync

Connections	- - outside: central power supply with main switch and protective cap, optional accessories
Data of currents	- 100 - 240 V - max. 10 A
Dimension of pockets	28 x 213 x 310 mm
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm



- UltraCharge charging unit with up to 20 slots
- charging indicator



- integrated temperature sensor protects from overheating
- automatic switch-off of charging function at a temperature over 50°C inside the case